

# HA 15



| HA15 E1 |  |      |      |      |      |
|---------|--|------|------|------|------|
| kg      |  | 1195 | 675  | 450  | 320  |
| m       |  | 1,07 | 1,89 | 2,77 | 3,65 |

  

| HA15 E2 |  |      |      |      |      |
|---------|--|------|------|------|------|
| kg      |  | 1115 | 635  | 440  | 320  |
| m       |  | 1,13 | 1,95 | 2,77 | 3,65 |



| MODELS  | LIFTING MOMENT | MAX VERTICAL REACH (HYDR) | SLEWING ANGLE | SLEWING TIME | MAX WORKING HEEL | WORKING PRESSURE | CRANE WEIGHT WITHOUT STABILIZERS | OIL TANK CAPACITY | OIL FLOW | DIMENSIONS<br>mm B x h x S |
|---------|----------------|---------------------------|---------------|--------------|------------------|------------------|----------------------------------|-------------------|----------|----------------------------|
|         | tm             | m                         | °             | s/180°       | °                | bar              | kg                               | l                 | l/min    |                            |
| HA15 E1 | 1,28           | 2,98                      | 335           | 10           | 3                | 160              | 174                              | 17,5              | 8        | 620x1241x430               |
| HA15 E2 | -              | 3,80                      | 335           | 10           | 3                | 160              | 193                              | 17,5              | 8        | 672x1241x430               |