

**EDGE** LINE

# HB 240



## HB240 E2

|    |        |      |      |      |
|----|--------|------|------|------|
| kg | 22700* | 5280 | 3610 | 2750 |
| m  | 1,00   | 4,30 | 6,20 | 8,10 |

## HB240 E3

|    |        |      |      |      |       |       |       |       |
|----|--------|------|------|------|-------|-------|-------|-------|
| kg | 21865* | 5085 | 3425 | 2570 | 2035  | 1530  | 1170  | 770   |
| m  | 1,00   | 4,30 | 6,20 | 8,10 | 10,13 | 12,25 | 14,46 | 16,59 |

## HB240 E4

|    |        |      |      |      |       |       |       |       |       |
|----|--------|------|------|------|-------|-------|-------|-------|-------|
| kg | 21155* | 4820 | 3215 | 2380 | 1880  | 1530  | 1170  | 915   | 735   |
| m  | 1,00   | 4,39 | 6,29 | 8,19 | 10,22 | 12,25 | 14,46 | 16,59 | 18,70 |

## HB240 E5

|    |        |      |      |      |       |       |       |       |       |
|----|--------|------|------|------|-------|-------|-------|-------|-------|
| kg | 21490* | 4585 | 3033 | 2220 | 1710  | 1390  | 1170  | 915   | 735   |
| m  | 1,00   | 4,47 | 6,37 | 8,27 | 10,30 | 12,33 | 14,46 | 16,59 | 18,70 |

\*) Theoretical lifting capacity

# HB 240



**EES Extra Extension Speed**  
**SDS Smooth Descent System**

| MODELS   | LIFTING MOMENT | MAX VERTICAL REACH (HYDR) | SLEWING ANGLE | SLEWING TIME | MAX WORKING HEEL | WORKING PRESSURE | CRANE WEIGHT WITHOUT STABILIZERS | OIL TANK CAPACITY | OIL FLOW | DIMENSIONS    |
|----------|----------------|---------------------------|---------------|--------------|------------------|------------------|----------------------------------|-------------------|----------|---------------|
|          | tm             | m                         | °             | s/180°       | °                | bar              | kg                               | l                 | l/min    | mm B x h x S  |
| HB240 E2 | 18,9           | 11,9                      | 415           | 20           | 4                | 320              | 2375                             | 130               | 80       | 2520X2300X930 |
| HB240 E3 | -              | 13,9                      | 415           | 20           | 4                | 320              | 2530                             | 130               | 80       | 2520X2300X930 |
| HB240 E4 | -              | 16,0                      | 415           | 20           | 4                | 320              | 2680                             | 130               | 80       | 2520X2300X930 |
| HB240 E5 | -              | 18,2                      | 415           | 20           | 4                | 320              | 2800                             | 130               | 80       | 2520X2300X930 |