

EDGE LINE

HC 91



HC91 E1

kg	8340*	2000	1400
m	1,00	4,17	5,98

HC91 E2

kg	3900*	935	1330	1015	720	515
m	1,00	4,17	5,98	7,79	9,82	11,85

HC91 E3

kg	7630*	1795	1210	910	720	515	355
m	1,00	4,25	6,06	7,87	9,82	11,85	14,00

HC91 E4

kg	7380*	1705	1130	830	640	515	355	280
m	1,00	4,33	6,14	7,95	9,90	11,85	14,00	16,18

HC91 E5

kg	7040*	1600	1040	710	535	430	355	280
m	1,00	4,40	6,21	8,02	9,97	11,92	14,00	16,18

*) Theoretical lifting capacity

EDGE
LINE

HC 91



EES Extra Extension Speed
SDS Smooth Descent System
LAS Liftrod Articulating System

MODELS	LIFTING MOMENT	MAX VERTICAL REACH (HYDR)	SLEWING ANGLE	SLEWING TIME	MAX WORKING HEEL	WORKING PRESSURE	CRANE WEIGHT WITHOUT STABILIZERS	OIL TANK CAPACITY	OIL FLOW	DIMENSIONS
	tm	m	°	s/180°	°	bar	kg	l	l/min	mm B x h x S
HC91 E1	8,4	9,3	425	20	4	315	1105	75	40	2290X2085X800
HC91 E2	-	10,9	425	20	4	315	1195	75	40	2290X2085X800
HC91 E3	-	13,1	425	20	4	315	1285	75	40	2300X2085X800
HC91 E4	-	15,1	425	20	4	315	1370	75	40	2300X2085X800
HC91 E5	-	17,3	425	20	4	315	1445	75	40	2300X2085X845