

HC 243



- EES** Extra Extension Speed
- SDS** Smooth Descent System
- LAS** Liftrod Articulating System

MODELS	LIFTING MOMENT	MAX VERTICAL REACH (HYDR)	SLEWING ANGLE	SLEWING TIME	MAX WORKING HEEL	WORKING PRESSURE	CRANE WEIGHT WITHOUT STABILIZERS	OIL TANK CAPACITY	OIL FLOW	DIMENSIONS
	tm	m	°	s/180°	°	bar	kg	l	l/min	
HC243 E2	22,5	11,7	415	20	4	315	2315	130	80	2520x2300x935
HC243 E3	-	13,8	415	20	4	310	2455	130	80	2520x2300x935
HC243 E4	-	15,9	415	20	4	310	2595	130	80	2520x2300x935
HC243 E5	-	18,1	415	20	4	310	2720	130	80	2520x2300x935
HC243 E6	-	20,3	415	20	4	310	2825	130	80	2520x2300x935
HC243 E7	-	22,5	415	20	4	310	2945	130	80	2520x2300x1005
HC243 E8	-	24,8	415	20	4	310	3035	130	80	2520x2300x1005
HC243 E4J3	-	24,1	415	20	4	325	3255	130	80	2520x2715x1055
HC243 E5J3	-	25,6	415	20	4	330	3210	130	80	2520x2615x1055
HC243 E6J2	-	25,9	415	20	4	325	3100	130	80	2520x2605x1055