

**EDGE** LINE

# HC 243K



## HC243K E2

kg	22715*	6090	4455	3190
m	1,00	3,72	5,06	7,03



## HC243K E3

kg	21875*	5865	4255	3010	2305
m	1,00	3,73	5,06	7,03	9,10

## HC243K E4

kg	21145*	5550	4005	2800	2115	1710
m	1,00	3,81	5,14	7,11	9,18	11,25

\*) Theoretical lifting capacity

# HC 243K



- EES** Extra Extension Speed
- SDS** Smooth Descent System
- LAS** Liftród Articulating System

MODELS	LIFTING MOMENT	MAX VERTICAL REACH (HYDR)	SLEWING ANGLE	SLEWING TIME	MAX WORKING HEEL	WORKING PRESSURE	CRANE WEIGHT WITHOUT STABILIZERS	OIL TANK CAPACITY	OIL FLOW	DIMENSIONS
	tm	m	°	s/180°	°	bar	kg	l	l/min	mm B x h x S
HC243K E2	22,7	10,7	415	20	4	300	2245	130	80	2520x2300x930
HC243K E3	-	12,8	415	20	4	300	2385	130	80	2520x2300x930
HC243K E4	-	14,9	415	20	4	300	2525	130	80	2520x2300x930